




eximSafe – Lock Paving Mat

1120 x 1000 x 15 / 30 / 43 mm, flat rear side and/or drainage channel



1. PRODUCT DESCRIPTION

eximSafe Lock Paving Mats are perfect on every surface where shock absorbing, elastic attributes are desired. The puzzle mat system with precision cut joints will not pull apart or disconnect. eximSafe Lock Paving Mats are temperature-resistant, slip-proof, noise-reducing, weather and UV-resistant, water permeable, indecomposable, thermal isolating, easy to install and to relocate due to puzzle edges (no adhesive necessary) and eco-friendly.

2. EXAMPLES OF USE

Fitness areas and gyms, commercial and residential applications, leisure and sport facilities, paddocks, stables, horse walkers, etc.

3. AVAILABLE DIMENSIONS (in mm)

1120 x 1000 x 15 / 30 / 43, flat rear side and/or drainage channel

4. TECHNICAL DATA

m ² per pallet:	78	44	33
Weight per m ² (kg):	13.41	26.73	38.34
Density (kg/m ³):	870	870	870
Colours:	red, green, black, special colours on request		
Temperature resistance:	from - 40 up to + 80°C (long term), up to + 110°C (short term)		
Chemical resistance:	resistant to weak acids and bases, conditionally resistant to oils		
Dimension deviation:	max. 1.5 %		
Recommended base:	concrete, asphalt, sand bed, paving		

5. MATERIAL

Rubber granulates from tyres, bonded with coloured, UV-resistant polyurethane.

6. INSTALLATION

Joint by puzzle edges, adhesive not a must (see eximSafe installation guide).

